Model YZ101



YZ101-CI/CII-W or B-V With Pressure Switch



YZ101-CI/CII-L-U Less Pressure Switch Shown w/ MF-8 Universal Mounting Flange



Product Description

Model YZ101 is a Type Y or Z pressurization unit designed to protect electrical equipment in Class I and Class II hazardous locations. When connected to a supply of protective gas, the Model YZ101 will supply, regulate and monitor the protective gas supply to a protected electrical enclosure. Type Z applications reduce the hazardous location rating inside the enclosure from Division 2/ Zone 2 to non hazardous. This allows general purpose equipment to operate in Division 2/ Zone 2 areas. Type Y applications reduce the hazardous location rating inside the enclosure from Division 1/ Zone 1 to Division 2/ Zone 2. This allows Division 2/ Zone 2 equipment to operate in Division 1/ Zone 1 areas.

A **DMI Model PV-3** spark arresting Purge Vent installed on the protected enclosure **OR** a **DMI Model RR-4** Redundant Regulator (or equivalent) installed upstream of the Model YZ101 Pressurization Unit is required for safe operation.

This unit is designed to meet or exceed NEC - NFPA 70, NFPA 496, EN 50016 and IEC 60079-02 requirements.

Unit Specifications

Recommended Max. Enclosure Volumes:

Class I Applications:	* 2 cubic feet
Class II Applications:	* 50 cubic feet
Protective Gas Supply:	Air or Inert Gas
Unit Supply Pressure:	
w/ Purge Vent:	80 - 125 psi max.
w/ Redundant Regulator:	5 psi max.
Unit Supply Connection:	1/4" tube fitting
Enclosure Supply:	1/4" tube fitting
Enclosure Reference:	1/4" tube fitting
Safe Enclosure Pressure:	0.5″ w.c. / 55Kb
Safe Press. Flowrate:	** 0.1 - 3.5 scfh per cf
* Contrat Fratew, for applications with larger endeaver values	

Contact Factory for applications with larger enclosure volumes * Enclosure Integrity determines actual Flowrate

Material Specifications

Unit Mounting Plate: Regulator body: Regulator Handle: Enclosure Press. Gauge: Tubing: Tube Fittings: Start up Labels: Enclosure Warning Label: 316 SS Brushed Enamel Finished Zinc Polycarbonate Enameled Alum. 316 Stainless Steel 316 Stainless Steel Silkscreened Lexan 316 Stainless Steel

D&**M I**nstruments, Inc.


Ph. 281-557-1002 Fax: 281-557-0703 League City, Texas USA www.dminstruments.com sales@dminstruments.com

A CONTRACTOR OF CO

YZ101-CI/CII-W or B-H With Pressure Switch

Copyright © 2004 D&M Instruments, Inc.

Document Control # YZ101SDS-R1.0



Copyright © 2004 D&M Instruments, Inc.